



Stock number: 1000262

- Single SPDT relay with LED
- Double-sided adhesive tape
- Mounting screw
- 12" leads
- 6 wire nuts

Power Requirements: Per position - 0.015 Amps @ 24VDC, 24VAC, 115VAC

Relay: UL recognized SPDT

Contact Rating: 10 Amps @ 115VAC

7 Amps @ 28VDC

250 Microamps @ 5VDC

Ambient Temperature: 32°F to 120°F (0°C to 49°C)

Approvals: UL Listed

Dimensions: 1.5" (38.1 mm) H x 1" (25.4 mm) W x 0.875" (22.2MM) D
12" (304.8mm) 18 ga. wire leads

Product Description

The PAM-1 Relay is an encapsulated 24VDC multi-voltage device providing 10.0 Amp form C contacts. The relay may be energized by one of three input voltages: 24 VAC, 24 VDC, or 115 VAC.

A red LED is provided which, when illuminated, indicates the relay coil is energized.

The PAM-SD may be mounted by using the double-sided adhesive tape, the self-drilling screw, or loosely placed in an electrical backbox.

These devices are ideal for applications where remote relays are required for control or status feedback. They are suitable for use with HVAC, temperature control, fire alarm, security, energy management, and lighting control systems.

Installation Wiring

