


TOP VIEW - HS24 & S24 MODELS

FRONT VIEW BRACKET



WIRING DIAGRAM - SEE INSTALLATION MANUAL FOR ADDITIONAL DETAIL


NOTES:

THIS UNIT IS DESIGNED FOR MOUNTING TO MOST SINGLE GANG BOXES, 4" SQUARE BOXES, 2-GANG MASONRY BOXES OR NON-METALLIC 2-GANG SWITCH BOXES

CONDUIT ENTRANCE TO BOXES SHOULD BE SELECTED TO INSURE SUFFICIENT WIRING CLEARANCE


RUN A MINIMUM 18 GAUGE INSULATED 2 OR MORE CONDUCTOR CABLE

THIS DRAWING INCLUDES REPRESENTATIVE DIMENSIONS FOR POTTER PRODUCT MODELS HS24, S24, & EH24.




CENTER LINE OF BOX TO TOP EDGE OF LENS HS24 & S24 MODELS

CENTER LINE OF BOX TO BOTTOM EDGE OF LENS GEC & GES MODELS




RIGHT VIEW - HS24 AND S24 MODELS




REAR VIEW - HS24, S24, EH24 MODELS

FRONT VIEW - HS24 AND S24 MODELS


CENTER LINE OF BOX TO HORN CENTER HS24 & EH24 MODELS




BOTTOM VIEW - HS24 & S24 MODELS



FRONT VIEW - EH24 MODELS



RIGHT VIEW - EH24 MODELS



ISOMETRIC VIEW